

| WARNING | | F | | INCH[MM] | | | |
|--|---|--|--|---------------------------|-----|--------------------------------------|---------------------------|
| PRODU TO TH | PORT OR RE-EXPORT OF THIS DRAWING OR A CT PRODUCED BY THIS DRAWING IS SUBJECT U.S. EXPORT ADMINISTRATION REGULATIONS HER APPLICABLE MATERIAL-RELATED LAWS, | UNLESS OTHERWISE SPECIFIED MACHINE SURFACE MAX. ROUGHNESS 125 μ in / 3.2 μ | | | | | |
| DIRECTIVES, OR REGULATIONS SUCH AS THOSE DEFINED IN BOBCAT STANDARD PR-CH. | | | | |] | X | ζ η η / Χ ξ |
| COPYRIGHT® | | | | | | | |
| IDENTI | ORIGINALLY CREATED AND REVISED IN THE YEARS AS IDENTIFIED IN THE RELEASING ECN. BOBCAT COMPANY RESERVES ALL RIGHTS. | | | THIRD ANGLE PROJECTION | | | MBOL WS A |
| THIS DOCUMENT CONTAINS CONFIDENTIAL AND TRADE SECRET INFORMATION, IS THE PROPERTY OF BOBCAT COMPANY, AND IS GIVEN TO THE RECEIVER IN CONFIDENCE. THE RECEIVER, BY RECEPTION AND RETENTION OF THE DOCUMENT, ACCEPTS THE DOCUMENTS IN CONFIDENCE AND AGREES THAT, EXCEPT AS AUTHORIZED IN WRITING BY BOBCAT COMPANY, IT WILL (1) NOT USE THE DOCUMENT OR ANY COPY THEREOF OR THE CONFIDENTIAL OR TRADE SECRET INFORMATION THEREIN; (2) NOT COPY THE DOCUMENT, (3) NOT DISCLOSE TO OTHERS EITHER THE DOCUMENT OR THE CONFIDENTIAL OR TRADE SECRET INFORMATION THEREIN: AND (4) UPON COMPLETION OF | | | CHARACTERS) OR < TEXT > PER BOBCAT STD P | | | | |
| | | | 2 | | | | |
| | | | | | | | |
| | | | • | | | | |
| | | | • | | | | |
| | | | INITIAL ECN: ECN000000 TITLE: HOS | | | | |
| | | | | 2.36 lb I.072 kg | S/A | 349.93 in ² 2257.60 cm | |
| 3 | | | | 2 | | | |